Rev: 2025-03-18

SC50BS SeriesESD Washable Cleanroom Shoe Cover

Reusable ESD-Safe Shoe Cover Provides Barrier Protection from Contamination & ESD Grounding

- ESD Shoe Cover with 3 layer dissipative rubber soft sole
- Replaceable 10" conductive ribbon for contact with the body
- Adjustable heel snap.
- Conductive ribbon connected to sole with internal snap
- Dissipative sole & ESD canvas fender—<3.5x10e7
- ESD cleanroom fabric cut (99% Polyester, 1% carbon fiber)
- Meets requirements of ANSI-ESD S20.20 and ANSI-ESD STM9.1—Footwear



Laundry Instructions

- Launder garment with cool or warm deionized water.
- Use neutral detergent preferably liquid.
- Do not use laundry detergents with softeners or bleach.
- Tumble dry with low heat or hang dry. Garment will dry quickly.
- To ensure a longer lifetime on garments avoid laundry high heat exposure.





Surface Resistance: 10 ⁷ Wash Test: 100	TX4000 99% polyester, 1% Carbon 10 ⁷ 100 washes White, Light Blue								White SC50BSWH01 SC50BSWH02 SC50BSWH03 SC50BSWH05 SC50BSWH05 SC50BSWH06	Light Blue XS SC50BSLB01 S SC50BSLB02 M SC50BSLB03 L SC50BSLB04 XL SC50BSLB05 2XL SC50BSLB06	XS S M L XL 2XL		
Part	XS	S	М	L	XL	2XL	3XL	4XL	5XL	SC50BSWH07 SC50BSWH08	3XL 4XL	SC50BSLB07 SC50BSLB08	3XL 4XL
A. Top Circumference	10.5	10.5	10.5	11	11	11	11	11	11	SC50BSWH09	5XL	SC50BSLB09	5XL
B. Sole Length 11		11.5	12	12.5	13	13.75	14.25	14.75	15.25		Replaceable Gro	unding Ribbons:	
C. Height of Sole Cover	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5		. GR10	10" 18"	
D. Conductive Ribbon Leng	gth 18	18	18	18	18	18	18	18	18		GR18 GR24		

This document is prepared for our customers as a service, and is to the best of our knowledge true and accurate. However, it is understood and agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.